



APK ID Delta Tag is passive RFID rugged hard tag that delivers exceptional performance specially when attached to metal surfaces like iron, steel, aluminum etc.

Features:

- Tag is built to withstand harsh environment & chemical exposure
- Work seamlessly on all metallic surfaces.
- Dust and water proof
- Optional configuration for free air application

Applications:

- Cargo and container tracking
- Automotive conveyances
- Returnable assets
- Industrial tools and equipment
- Warehouse racks and storage
- Forklifts and heavy machinery

Tag Specification Data

| | Low Frequency | High Frequency | Ultra High Frequency |
|---------------------|---|----------------------|----------------------|
| ISO Protocol | ISO 18000-2 | ISO 14443/ ISO 15693 | ISO 18000-6C |
| Operating Frequency | 125kHz/134.2kHz | 13.56MHz | 865-868/902-928MHz |
| IC Type | NXP, Silicon craft, Atmel EM, Texas Instruments | NXP, Legic, Infineon | Alien, NXP |
| Memory | IC dependent | IC dependent | IC dependent |
| Data Retention | Up to 10 years | Up to 10 years | Up to 50 years |
| Programming Cycle | Up to 100,000 cycles | Up to 100,000 cycles | Up to 100,000 cycles |
| Material | PC / ABS | PC / ABS | PC / ABS |
| Dimension | 28x28x8mm | 28x28x8mm | 28x28x8mm |
| Weight | Max 9.0g | Max 8.0g | Max 10.0g |

Environmental Test Data

| | |
|-----------------------|--|
| Ingress Protection | IP67 |
| Storage Temperature | -5°C to +80°C |
| Operating Temperature | -5°C to +80°C |
| Vibration Resistance | Excellent |
| Shock Resistance | Excellent |
| Impact Resistance | Good |
| Chemical Resistance | Highly resistive to Water Washing agents Ethanol Detergents Most oils and greases. |

APK Identification,
Plot#129-B, NSEZ,
Phase-II, Noida U.P 201305
INDIA.
Tel. +91 120 2462331/2460231,
Fax. +91 120 2462332

APK Identification,
33 Rubicon Centre,
Broad Ground Road,
Redditch, B98 8YP,
UK.
Tel. +44 1527 517 610,
Fax +44 1527 517 615,