



Tag Specification Data

	Ultra-High Frequency
ISO Protocol	ISO 18000-63, EPC Class1 Gen2
Operating Frequency	860 - 960 MHz ETSI / FCC compliant
IC Type	Impinj, NXP, Alien
Memory	EPC : 96-bit / 128-bit TID : 64 bit /96 bit
Data Retention	Up to 50 years
Programming Cycle	Up to 100,000 cycles
Material	TPU
Dimension	117 X 70 mm
Weight	Approx. 13.0g

Environmental Test Data

Ingress Protection	IP67
Storage Temperature	-30°C to +80°C
Operating Temperature	-30°C to +80°C
Vibration Resistance	Excellent
Shock Resistance	Excellent
Impact Resistance	Good
Chemical Resistance	Highly resistive to Washing agents, Ethanol, Detergents, Oils and greases.

FEEDLOT TAG

The APK-ID Feedlot tag is a specially designed tag using the latest in technology and manufacturing processes. UHF Feedlot tag having an inductively coupled antenna it delivers an exceptional reading range performance and long-term reliability.

Manufactured from premium quality materials and a high-quality metal tip so that the tag will pierce the animal's ear efficiently and provide excellent longevity. Tags can be custom-Laser printed with any text, barcode, QR code, logos, or numbers.

Features:

- · Designed specifically for ear tagging
- Compact & lightweight
- Tag is built to withstand harsh environment & Chemical exposure
- UV resistant
- · Dust and waterproof
- Metal tip
- · Excellent retention
- High quality RFID IC
- · Also available in various memory and ISO protocols

Applications:

- Livestock identification
- Livestock tracking

heet

APK Identification, Plot#129-B, NSEZ, Phase-II, Noida U.P 201305 INDIA. Tel. +91 120 2462331/2460231 Fax. +91 120 2462332

APK Identification, Greenlands Business Centre, Studley Road,Redditch,Worcs, B987HD, United Kingdom. Tel. +44 1527 517 610 Fax +44 1527 517 615